



Kusel Finishing Table with 2M4-17 Agitator shown

FINISHING TABLE

Kusel Finishing Tables continue to perform efficient and flexible curd and whey separation year after year because they are designed with strength.

KEY FEATURES

- Built according to 3-A standards for superior sanitation.
- The table is designed with a comprehensive slat rack underneath the pan liner for additional support.
- Kusel's heavy-duty construction makes for a table which can handle the most demanding applications for a lifetime.
- Incredibly strong construction under the pan to virtually eliminate any warping.
- The Kusel Finishing Table is designed to seamlessly integrate with the 2M4-17 Agitator.
- The agitator supports feature box tube construction. Supports include double posts at the rear end, a bridge at the front end, and a double post support at the center for tables over 40 feet.

STANDARD TABLE SIZES

- Length: 15 to 60 feet
- Width: 58 to 72 inches
- Depth: 14, 16, or 18 inches
- Outlet: 3 or 4 inches
- Screens: 5 inch wide
- Available in custom sizes to fit your requirements

CONSTRUCTION

- Rear end drain outlet
- Center bottom pan drain trough with removable, slotted, stainless-steel screens runs the length of the table
- Whey outlet in trough
- Unloading door at front of table with standard pivot crank door latches and sanitary gasket
- 12-gauge (10-gauge optional) #2B finish stainless steel inner pan liner
- 12-gauge, stainless-steel exterior sides, ends, and bottom
- Continuously welded at the rail for improved sanitation and strength
- Square front end
- Round rear end, with "hex-shaped" exterior (square rear end optional)

STANDARD OPTIONS

- 7 inch wide slotted, stainless-steel drain screens
- 10 inch wide slotted, stainless-steel drain screens (double wide 5 inch screens)
- 10-gauge inner pan liner
- Jacketed heating with dual stainless-steel steam pipes
- Custom door latches designed to customer needs
- Square rear end
- Pre-draw outlet